



elio VRP základ TAB 10"+ tlačiareň XP-58IIBT

Elio VRP základ obsahuje v zostave tablet ULTIMATE 10" Android, POS tlačiareň elio XP-58IIBT a aplikáciu elio driver VRP.. Tlačiareň s tabletom je prepojená cez Bluetooth.

elio POS tiskárna XP-58IILB USB+BLUETOOTH
Maximalizujte svoj obchod s POS tlačiariňou elio XP-58IIL. Vstavaný napájací zdroj, ľahké prenášanie a výrazné ušetrenie pracovného priestoru pokladníka, to sú najväčšie výhody POS tlačiarene elio XP-58IIL. Tlačí na pásku šírky 58mm, prepojenie cez USB alebo BLUETOOTH, bez nožničiek .

Printing

Printing method Direct thermal

Printing width 48mm

Column capacity 384 dots/line

Printing speed 90mm/s

Interface USB + Bluetooth

Paper width 57.5±0.5mm×φ60mm

Line space 3.75mm (changeable using commands)

Character size ANK, Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) simplified/traditional Chinese : 3.0×3.0mm (24×24 dots)

Barcode Character

Code page PC347 (Standard Europe) , Katakana, PC850 (Multilingual) , PC860 (Portuguese) , PC863 (Canadian-French) , PC865 (Nordic) , West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2) , PC852 (Latin2) , PC858, IranII, Latvian, Arabic, PT151 (1251)

Barcode UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128

Power

Power supply input 12VDC, 2.6A

Physical characteristics

Gross weight 0.79kg

Dimensions 185×132×110mm (D×W×H)

Environmental Requirements

Work environment 0~45°C, 10~80% RH

Storage environment -10~60°C, 10~90% RH (no condensation)